



Thinking about performance: Quality products designed to perform

Scantronic 760 External Wireless Sounder













The Scantronic 760 is an EN50131, PD6662:2004 Grade 2, external radio sounder incorporating Scantronic's advanced 868MHz narrowband radio technology. The 760 is designed with features such as a built in spirit level and adjustable screw holes making it quick and easy to install.

- 100m range in free air
- 868MHz radio technology from the market leaders
- Anti-Jamming protection built into the unit
- Quiet installation mode
- Compatible with



Additional Features

Standards	EN50131, PD6662:2004 Grade 2
Speedy Installation and	Built-in spirit level
Maintenance	Adjustable screw holes enable levelling without re-drilling
	Logo screen-printing service available
	Low battery warning on panel
	Choice of battery options: Alkaline or Lithium
	Quiet installation mode
Flexible	Multiple sounders can be used on a single installation
	Selectable cut-off timer 3mins-15mins
Secure	Anti-Jamming protection built into the unit
	Cover and adjustable rear tamper fitted
	Conformal coated electronics
	High impact resistant 3mm polycarbonate back-plate and cover with tamper front and rear


Specification

Model	Description
760ES	
EN50131 Grade	2
Environmental Class	IV
No of Piezo's	2
Sound Output (dbA at 1m)	105
Operating Voltage	Nominal 2 x 3v Alkaline or 1 x 7.2v Lithium
Battery Life	2 Years with typical use
Replaceable Battery	Yes
Battery Status Monitor	Yes
Cut Off Timer	5 seconds, 3 minutes or 15 minutes
Silent Engineer Mode	Yes
Siren Trigger	Radio
Strobe Trigger	Radio
Tamper Detection	Cover / Rear
Tamper Signal	Radio
Jamming	Yes
Base Plate	Polycarbonate
Outer Cover	3mm polycarbonate
External Dimensions	346h x 212w x 76d

Part Numbers

Part Number	Product Description
760ES	External radio sounder with cover and alkaline battery pack
760DS	Decoy sounder complete with cover
760CV	Cover Only
760EB	Working backplate with alkaline battery pack (no cover)
760DB	Decoy backplate (no cover)
760SB	Alkaline battery pack
760LB	Lithium battery pack (for use where the temperature regularly drops below 0°C)

Installer Details:



For information on your local stockist contact our Marketing Department

telephone: +44 (0)1594 541 979

fax: +44 (0)1594 545 445 email: marketing@coopersecurity.co.uk